





	TOP PRICE- PERFORMANCE		TOP ACCURACY		TOP COOLING	TOP SAFETY	SQUARE DRIVE			
										
	GERC-B	GERC-BD	GERC-HP	GERC-HPD	GERC-HPDD	GERC-W	GERC-WD	GERC-GBD	GERC-GBDD	
										
DIN ISO 15488	✓	✓	✓*	✓*	✓*	-	-	✓	✓	
CONCENTRICITY	5 µm	5 µm	2 µm	2 µm	2 µm	3 µm	3 µm	10 µm	10 µm	
CLAMPING DIAMETER BRIDGING	0,5 - 1 mm	h8	h10	h8	h8	h8	h8	h8	h8	
SEAL FOR IC (INTERNAL COOLING) RUBBER SEAL	-	✓ (up to 60 bar)	-	✓ (up to 60 bar)	-	-	✓	✓ (up to 60 bar)	-	
SPRAY NOZZLES FOR IC (THROUGH COLLET)	-	-	-	-	✓	-	-	-	✓	
INTERNAL SQUARE DRIVE FOR TAPS	-	-	-	-	-	-	-	✓	✓	
PRECISION COLLET CHUCK CENTROJP	possible/ not recommended	possible/ not recommended	recommended	recommended	recommended	possible/ not recommended	possible/ not recommended	recommended	recommended	
ULTRA POWER CHUCK - UPC & FULL PERFORMANCE CHUCK - FPC	possible/ not recommended	possible/ not recommended	recommended	recommended	recommended	recommended	recommended	possible/ not recommended	possible/ not recommended	
STANDARD COLLET CHUCK DIN ISO 15488	recommended	recommended	possible/ not recommended*	possible/ not recommended*	possible/ not recommended*	not possible	not possible	recommended	recommended	
FAHRION Protect	✓	✓	✓	✓	✓	✓	✓	✓	✓	
AVAILABLE SIZES	ER8 ER11 ER16 ER20 ER25 ER32 ER40	ER11 ER16 ER20 ER25 ER32 ER40	ER8 ER11 ER16 ER20 ER25 ER32 ER40	ER11 ER16 ER20 ER25 ER32 ER40	ER11 ER16 ER20 ER25 ER32 ER40	ER11 ER16 ER20 ER25 ER32 ER40	ER32 ER40	ER32 ER40	ER16 ER20 ER25 ER32 ER40	ER16 ER20 ER25 ER32 ER40

* Only DIN ISO 15488 compliant after removal of the blue ring